



Attachment “B” – Safety Rules and Guidelines for Subcontractors

All persons are to comply with all safety rules and guidelines set forth by Triad Builders Safety Program. Triad Builders safety rules and guidelines are as follows:

Drug and Alcohol Policy:

- The use, sale, or possession of illegal narcotics, drugs, or alcohol substances is strictly prohibited. Any person or persons found with such substances while on the job site will be removed from the job immediately and may result in termination of subcontractor.

Safety Meeting Policy:

- There will be a brief safety meeting every Monday morning. Safety meetings will be given by the job site superintendent and will require all persons on job site to attend safety meeting.

Fall Protection Policy:

- All persons performing work that is 6' above lower level will be required to have fall protection system in place. The methods of fall protection will be guardrail systems that consist of top rails at 42" and mid rails at 21", a safety net system, or full body harness with lanyard. Roofers only may use a warning line system in conjunction with a safety monitor. The warning line will be installed 6' from the unprotected edges of the roof that does not have at least a 39" parapet wall or a guard rail system in place.

Personal Protection Policy:

- Hearing protection will be required when job site conditions require it or when noise levels exceed the standard limitations based on an eight-hour workday.
- All persons working on or visiting job site are required to wear a hard hat at all times.
- Hard soled shoes or boots are required at all times while on the job site.
- All persons will wear clothing suitable for work and weather conditions, short sleeve shirts and long trousers are a minimum.
- All persons whose work requires or who operates tools and equipment that have the potential for eye injuries will wear eye protection.

Scaffolding Policy:

- All persons having to work form scaffolding must have competent person on the job site at the time of erecting all scaffolding. All scaffolding will be set on wood mudsills with a minimum area of 2"x10"x18". All pins will be in place in all coupling areas. Scaffolding will be erected in a plumb condition. Bracing will be put on the front and back to connect end frames. All scaffolding 10 feet in height must have guardrail system on all sides except the side where work is being performed. All work platforms will be completely decked with voids no more than 1" between the decking boards.

Welding and Cutting:

- All persons where work requires welding or cutting torches must have fire extinguisher within 10 feet of working area at all times. A fire watch will also be required for at least 15 minutes after work is completed.

OSHA Standards:

- In addition to Triad Builders' Safety Rules and Guidelines, all persons are to comply with all OSHA standards and guidelines per subcontractor's trade of work.

Translation:

- Each crew must have at least one person who speaks fluent English on site at all times for translation and communication with the project superintendent.

Job Name: _____

Job Number: _____

Company Name: _____

Signature: _____ **X**

Date: _____